

10000 PSI Sample Cylinder - Titan



DESCRIPTION:

10000 PSI Sample Cylinder with piston and blending ball.

Suitable for use in any ambient condition to be expected outdoor, subject to the specified temp, limitations, including offshore platforms, onshore terminals and sites in tropical areas.

Valves in endcap with 1/4" NPT, female ports.

Transportation box available.

TYPE

Model:	10000 PSI Sample Cylinder
GA-drawing no:	MPC 10000
Net volume:	640 and 1000 cc
Filling pressure:	10000 psi @ 21 °C
Working temp.:	-20 to 100 °C
Material:	Titanium Grade 5 and grade 2. Valves in 316 SS
Net weight (kg):	7,5 kg
Dimensions (mm):	(OD x H x L) ø 65 x 130x 550 with valves.

Service:	Compressed Gas, Flammable N.O.S	UN 1954
	Hydrocarbon Gas Mixture	UN 1964
	Hydrocarbon Gas Mixture Liquefied , N.O.S	UN 1964
	H2S – Hydrocarbon Sulphide	UN 1053
	Liquefied gas, Flammable N.O.S	UN 3161
	Natural Gas with Metane content	UN 1971
	Nitrogen Compressed	UN 1066
	Crude Petroleum	UN 1267
	Petroleum Gas, Liquefied or Liquefied Petroleum Gas	UN 1075
	Compressed gas, toxic, flammable, N.O.S inhalation Hazard Zone B	UN 1953
	Formation Water,	Water with dissolved salts
	and various quantities and compositions.	

Please note that some of these fluids may not be accepted for Air Transport

DOCUMENTATION

Standard:	Certificate of conformity. Manufacturing Declaration of conformity with: 97/23/EC PED and 2010/36/EU TPED
-----------	--